Specification

Vormatic 49 LCD Display
подвесной



vormatic®
electronics

- Highlight window hanging advertising machine
- Multimedia information release system is a high-definition multimedia display technology that uses the display screen to display enterprise propaganda and real-time notification in an all-round way. The system combines audio and video, TV pictures, pictures, animation, text, documents, web pages, streaming media, database data, etc. into a segment of wonderful programs, and pushes the produced programs to the media display terminals distributed all over the world in real time through the network. In this way, wonderful pictures and real-time information can be perfectly displayed in a full range of designated places in front of the required masses.
- Traditional display brightness (300-350CD/m²) can not be viewed normally under direct sunlight during the day, ultra-bright screen brightness up to 3000CD/m² in high light, outdoor, window and other harsh conditions can be used freely.

Copyright © The Limited Liability VORMATIC

Technology parameters

Model number		WD49T-3（OD10 Optional wire rope hanger or hanging telescopic rod）
Appearance	Appearance color	Grey/White/Black optional/More than 10 sets can be customized color
	Body size	1147*637*57(L*W*T)
	Fuselage materia	Sheet metal
	Installation mode	Hanging type
Package	Package size	1340*250*890 MM
	Machine weight	42 kg
Display	dimension	49″TFT LED
	Display area/scale	1073.8mm x604 mm
	Maximum resolution	1920× 1080
	luminance	700cd/m2 2500cd/m2（Highlighter is optional 1000-3000）
	Contrast	1300:1
	Viewing Angle	(Up/down/left/right):89°/89°/89°/89°
	Response time	6ms
	hue	16.7M color
Power supply and power consumption		100V~240V AC, ≤320W
Main board	Port	RK3288, CPU 4 core 1.8GHz GPU 4 core Mali-T764 DDR3 Operating memory 2GB Storage 16GB (expandable) 2 USB external 4 USB built-in 1 SD 1 RJ45 network port 1 LVDS, 1 HDMI2.0 support 4K@60HZ output (need to be customized) Support wifi/ Bluetooth/scalable 3G, 4G
Feature	Operating system	Android 5.1.1
	Menu language	Chinese English Russian American English French Spanish and other multi-language menu
	Video support format	Support RM/RMVB，MKV，TS，FLV，AVI，VOB，MOV，WMV，

Copyright © The Limited Liability VORMATIC

	Audio support format	MPEG-1 Layers I、II、III2.0, MPEG-4 AAC-LC 5.1/HE-AAC 5.1/BSAC 2.0, WAV, 24-bit linear PCM 7.1
	Picture support format	BMP、JPEG、PNG、GIF
	Other supported formats	PDF、PPT、SWF、Text, real-time data streaming
	Picture segmentation	Video area, graphic area, scrolling subtitles, LOGO area, date area, time area, Week area, weather forecast area, live picture area, live video area...
	System upgrade mode	SD card update
	System management mode	Unified management, group management, multi-user management, remote management, timing switch
	Remote operation mode	Remote automatic switch, remote update edit play program, remote monitoring status
	System Play mode	Supports a variety of playback modes, such as loop, timing, and interjection
	System architecture	Adopts the advanced Browser/Server (B /S) management architecture
	Support network	Local Area Network, wide area network, WIFI, 3G
	Built-in speaker	Built-in mini dual speakers
Other	reliability	50000h
	Operating temperature	-10℃ ~50℃
	Storage temperature	-20℃ ~60℃
	Operating humidity	5% ~90%
	Storage humidity	5% ~90%
	Safety index	Supports hardware dongle, login password, control password, hierarchical user rights Settings
	Quality standard	China Electrical Products Compulsory Certification (3C)
	Environmental protection standard	All components and packaging accessories meet international environmental standards

Copyright © The Limited Liability VORMATIC

Appearance size

